



### CONTACT

Market information  
[industryprojects.business@lynxgroup.com](mailto:industryprojects.business@lynxgroup.com)

**INSTRUMENTATION, CONTROL AND COMMUNICATION cables**

### STANDARDS

**Product** IEC 60228

**Installation** IEC 60092-350; IEC 60092-360; IEC 60092-376

**Test a;** IEC 60332-1; IEC 60332-3-22; IEC 60754-1; IEC 61034

### APPLICATION

TX<sup>®</sup> (C) 150/250 V overall screened twisted pair cables are used for telecommunication and instrumentation purposes. These cables provide a medium protection against external electromagnetic disturbances. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

### Design

#### 1. Conductor

Stranded bare copper class 2

#### 2. Insulation

XLPE (cross-linked polyethylene)

#### 3. Collective screen

Alu/polyester tape with a tinned copper drain wire

#### 4. Outer sheath

Polyolefin SHF1  
 Colour : grey

Example of marking

LYNXEO 279 TX(C) Nbr of pairs/triads & cross-section 150/250V 90C IEC 60092-376 IEC 60332-3-22 Cat. A WW YYYY \*CE\* Manufacturing n°+ metric marking

Core Identification

Pair: white / blue with printed with pair number

Triad: white / blue / red with printed with triad number



Conductor flexibility  
**Stranded class 2**



Halogen free  
**IEC 60754-1**



Rated Voltage U<sub>o</sub>/U<sub>m</sub>  
**150 / 250 (300) V**



Fire retardant  
**EN IEC 60332-3-22 (cat A)**



Flame retardant  
**IEC 60332-1**



Smoke density  
**IEC 61034**



Gases corrosivity  
**IEC 60754-2**



Electro magnetic interference resistance  
**Yes**

**CHARACTERISTICS****Construction characteristics**

Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Aluminium/polyester tape
Drain wire	Tinned copper
Outer sheath	Polyolefin
Sheath colour	Grey
Halogen free	IEC 60754-1

**Dimensional characteristics**

Number of pairs	-
Number of triples	4
Conductor cross-section	1.5 mm <sup>2</sup>
Nominal outer diameter	15.0 mm
Minimum outer diameter	14.5 mm
Maximum outer diameter	16.5 mm
Approximate weight	320 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	150 / 250 (300) V
Max. DC resistance of the conductor at 20°C	25.6 Ohm/km

**Usage characteristics**

Fire retardant	EN IEC 60332-3-22 (cat A)
Flame retardant	IEC 60332-1
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-30 ... 80 °C
Max. conductor temperature in service	90 °C

**OTHER CHARACTERISTICS****Test Voltage**

AC between cores of the same unit..... 1.5 kV

**Minimum bending radius for fixed installations**

- cable diameter ≤ 25 mm..... 4 x outer diameter
- cable diameter > 25 mm..... 6 x outer diameter