



Country Ref.: Q102516E200

### CONTACT

Market information  
[industryprojects.business@lynxgroup.com](mailto:industryprojects.business@lynxgroup.com)

PUR control/signal cables for extremely dynamic and drag-chain application, TPU-jacket, shielded, oil resistant, flame retardant, halogen free, UL and CSA approved

### STANDARDS

Product UL and CSA approval

Cables designed for continuous moving application, high flexible, oil resistance, halogen free

Applications:

- Tracksystems for tool machines
- Wood machines
- Automatic lines for assembly
- Handling
- Packaging
- Other applications with moderate stresses

## CHARACTERISTICS

(16x0,25)C

Insulation colour	DIN 47100
Taping	Non woven tape
Shielding	85% tinned copper braid coverage
Sheath colour	PUR
Halogen free	Grey RAL 7001

	0.25 mm <sup>2</sup>
	16
	7.5 mm
Copper content	55.1 kg/km
( )	87 kg/km



Halogen free



Operating temp.  
-30 ... 80 °C



Storage temperature, range  
-40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance  
EN 50363 - 10 - 2

Rated Voltage Uo/U	300 V 1500 V
Bending cycles	10 Mio.
Speed	600 m/min
Maximum acceleration	60 m/s <sup>2</sup>
Field of application	Dynamic
操作度范	- 30 ... 80 °C
Minimum dynamic operating bending radius	6.5 (xD)
Storage temperature, range	- 40 ... 80 °C
	IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1
Oil resistance	EN 50363 - 10 - 2



Halogen free



Operating temp.  
- 30 ... 80 °C



Storage temperature, range  
- 40 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1



Oil resistance  
EN 50363 - 10 - 2