



Country Ref.: C1B10056409

CONTACT

Market information
industryprojects.business@lynxgroup.com

UL - listed tray cables (TC - ER) cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, shielded, oil resistant, flame retardant, TC - ER and MTW approved, UL Listed. suitable for American and Canadian market

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- cable tray in factories in industry
- Industrial sector
- wind turbine application

Approvals:

UL MTW UL1063

UL TC - ER 90 ° C 600V UL1277

UL WTTC 90 ° C 1000V UL2277

UL DP - 1

UL AWM 600V

C(UL) CIC/TC

CHARACTERISTICS

(5G10)C

PVC/Nylon

Insulation colour

Black w. number + yellow/green

Drain wire

Shielding

85% tinned copper braid coverage

Sheath colour

10 mm²

5

23.3 mm

Copper content

555 kg/km



Operating temp.
-5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes

()	1005 kg/km
Rated Voltage U _o /U	600 V 2000 V
Field of application 操作度范	Fixed installations - 5 ... 90 ° C
Minimum bending radius, static (XD)	20 UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.
-5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes