



Country Ref.: B1B10056409

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

- UL MTW UL1063
- UL TC-ER 90°C 600V UL1277
- UL WTTC 90°C 1000V UL2277
- UL DP-1
- ULAWM 600V UL758
- C(UL) CIC/TC

CHARACTERISTICS

Construction characteristics

Construction type	5G10
Conductor material	Annealed copper
Insulation	-
Insulation colour	Black w. number + yellow/green
Outer sheath	Special PVC compound
Sheath colour	Black

Dimensional characteristics

Conductor cross-section	10 mm ²
Number of cores	5



Operating temp.
-5 ... 90 °C



Flame retardant
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes

Dimensional characteristics

Outer Diameter	21.5 mm
Copper content	480 kg/km
Approximate weight	880 kg/km

Electrical characteristics

Rated Voltage U ₀ /U	600 V
Test voltage	2000 V

Usage characteristics

Field of application	Fixed installations
Operating temperature, range	-5 ... 90 °C
Minimum bending radius, static (XD)	15
Flame retardant	UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.
-5 ... 90 °C



Flame retardant
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes